




Model: **A60IVX**
Diesel Generator Set



FEATURES

- Konar provides one-source responsibility for the generator system and its accessories.
- All units and components are factory tested during prototype and manufacturing stages assuring long product life.
- Generator set accepts one-step 100% of full load per NFPA 110.
- A **one-year** limited **warranty** covers all systems and components. Extended warranties are available.
- Rugged 4 cycle heavy-duty diesel engine, with swirl intake ports for a low fuel consumption and excellent transient response.
- **Generator features:**
 - Unique Volts per Hertz compensated electronic AVR excitation system delivers reliable voltage response for in rush loads.
 - Brushless, rotating-field generator has low reactance, 2/3 pitch, class H insulation, minimizes voltage distortion when powering non-linear loads.
- **More features:**
 - Controllers are available to meet your most demanding applications.
 - In the event of low oil pressure or high coolant temperature the self-protecting system will automatically stop the engine.
 - Aluminum Enclosure Sound Attenuated
 - Integrated fuel Tank – 150gal single wall or optional 80gal double wall UL142 listed

GENERATOR SET RATINGS

Model	Volt Code	Voltage	Winding Connection	Phase	Power Factor	Hz	Amps Standby	Standby kW / kVA	Prime kW / kVA
A60IVX	60	600 / 346	12 - HI WYE	3	0.8	60	72	60 (75)	52 (65)
A60IVX	61	480 / 277	12 - HI WYE	3	0.8	60	90	60 (75)	52 (65)
A60IVX	63	440 / 254	12 - HI WYE	3	0.8	60	99	60 (75)	52 (65)
A60IVX	64	240 / 139	12 – HI DELTA	3	0.8	60	181	60 (75)	52 (65)
A60IVX	65	220 / 127	12 – LOW WYE	3	0.8	60	197	60 (75)	52 (65)
A60IVX	66	208 / 120	12 – LOW WYE	3	0.8	60	208	60 (75)	52 (65)
A60IVX	67	240 / 120	12 – 2 DELTA	1	1.0	60	250	60 (60)	52 (52)
A60IVX	51	415 / 240	12 – HI WYE	3	0.8	50	90	52 (65)	47 (58)
A60IVX	53	380 / 220	12 – HI WYE	3	0.8	50	99	52 (65)	47 (58)
A60IVX	55	220 / 127	12 – LOW WYE	3	0.8	50	171	52 (65)	47 (58)
A60IVX	57	220 / 110	12 – 2 DELTA	1	1.0	50	236	52 (52)	47 (47)

Stand-By ratings are continuous electrical service during the interruption of normal power. No overload capacity is specified at these ratings. Prime ratings available with variable loads are continuous, 10% overload capacity for one hour in twelve hours periods.

Both ratings per BS 5514, DIN 6271, ISO-3046
 600 Voltage available only with Stamford alternator.

ALTERNATOR SPECIFICATIONS

Type	Four pole, revolving field
Rotor Insulation	Class H
Temperature Rise	150°C Standby
Material	Epoxy resin
Line-To-Line Harmonic Factor (Max)	5%
Telephone Interference Factor (Tif)	1%
Voltage Regulator	Solid State
Cooling	Self-ventilated and drip proof
Bearing	1 each, pre-lubed
Coupling	Direct, Flexible Disc
Load Capacity (Standby)	100%
Overload Capacity (Prime)	110%
Voltage Regulation	
No Load To Full Load	±1 %
One Step Load Acceptance	
Per NFPA 110	100%

- ❑ Four pole, revolving field, direct coupled to engine flywheel, provides excellent alignment.
- ❑ Insulation is of class H, ready to be used on harsh environments where sea spray, sand and chemical corrosion are existing factors.
- ❑ Voltage regulator provides Volts/Hertz compensation to improve the motor starting capabilities, therefore support the engine handling transient loads.
- ❑ Dynamically balanced rotor, with damper winding, help dissipate transient voltage interference during load variations.
- ❑ The windings have a 2/3 pitch in order to reduce the harmonic content of voltage.
- ❑ Robust mechanical structure permits easy access to connections.

ENGINE SPECIFICATIONS

Manufacturer	IVECO
Model	NEF45 SM1A
Bore	4.09 in. (104mm)
Stroke	5.19 in. (132mm)
Number Of Cylinders	4
Piston Displacement	274.60 in. ³ (4.5L)
Compression Ratio	17.5:1
Combustion System	Direct Injection
Engine Type	In-Line – 4 Cycle
Aspiration	Turbocharged after cooled air/air
Engine Crankcase Vent System	Closed
Cylinder	Borable
Crankshaft Material	Forged Steel
Governor, Make	Mechanical
Frequency Regulation,	
No Load To Full Load	5 %
Air Cleaner	Dry Element

- ❑ Robust industrial grade IVECO diesel engine, for reliable endurance.
- ❑ Direct fuel injection system and swirl intake ports combine for a low fuel consumption and excellent transient response.
- ❑ Cylinder Head provides superior airflow through specially designed intake manifold ports, large valves and seats resulting in superior engine performance in torque reserve, fuel consumption and emissions.
- ❑ Oil and filters interval for replacement every 600 hrs.
- ❑ Dynamically Balanced Crankshaft, with induction-hardened journal surfaces significantly increases wear life.
- ❑ Poly Belt Fan Drive provides superior noise and vibration reduction.

STANDARD EQUIPMENT

ENGINE

- Air Cleaner
- Fuel Pump
- Fuel Filter
- Oil Pump
- Full Flow Oil Filter
- Jacket Water Pump
- Thermostat and Housing
- Exhaust Manifold Dry
- Oil Cooler
- Blower Fan & Fan Drive
- Radiator - Unit Mounted
- Electric Starting Motor 12v
- Housing & Flywheel
- Charging Alternator - 12v

- Battery Kit & Battery Rack

GENERATOR

- Synchronous, Brush-less
- Four Pole
- Single Bearing
- Direct Coupled With Flex
- Class H Insulation
- Drip-Proof Construction

CONTROL PANEL

- Digital Control Panel
- Auto Start Module
- Electric Hour Meter
- Stop-Manual-Auto Pushbuttons

- Standard Engine Control Monitoring
- Automatic Shutdowns
- * High Water Temperature
- * Low Oil Pressure
- *Protective 12vdc Circuit Breaker
- Display Lights For:
 - * Water Temperature
 - * Oil Pressure
 - * Overcrank
 - * Underspeed
 - * Overspeed
 - * Battery Charging

GENERAL

- Rain Cap
- Oil Drainage kit
- Integrated Fuel tank
- Radiator Recovery Tank
- In Frame Lifting Points

INSTALLATION AND APPLICATION DATA

	Item	Units	Type of Operation and Application			
			60 Hz		50 Hz	
			Prime	Standby	Prime	Standby
Engine	Rated Speed	rpm	1800		1500	
	Gross Engine Output	bhp (kWm)	79 (59)	87 (65)	71 (53.5)	79 (59)
	BMEP	psi (kPa)	126 (871)	139 (960)	136 (940)	151 (1046)
	Mean Piston Speed	Ft/s (m/s)	25.8 (0.65)		21.5 (0.54)	
Cooling System	Ambient Air Temperature	°F (°C)	122 (50)			
	Engine Heat Reject to Coolant	BTU/min (kW)	2480 (0.72)			
	Pusher Fan Air Flow	Cfm (m3/m)	309 (8.75)			
	Coolant Flow	gal/min (L/min)	41.8 (158.33)			
	Coolant Capacity	qt (L)	9 (8.5)			
	Thermostat Start to Open	°F (°C)	83-95 (28-35)			
	Thermostat Fully Open	°F (°C)	103 (40)			
Fuel System	Fuel Type		Diesel #2			
	Fuel Consumption @ 50% Power	gal/hr (L/hr)	2.16 (8.2)		1.84 (7.0)	
	Fuel Consumption @ 80% Power	gal/hr (L/hr)	3.09 (11.7)		2.69 (10.2)	
	Fuel Consumption @ 100% Power	gal/hr (L/hr)	4.09 (15.5)		3.61 (13.7)	
Air Requirement	Combustion Air Flow	ft ³ /min (m ³ /min)	309 (8.75)			
	Air Intake Restriction	In.H ₂ O (kPa)	14 (3.5)			
	Exhaust Temperature	°F (°C)	905 (485)			
	Maximun Allowable Back Pressure	In.H ₂ O (kPa)	40.18 (10)			
Lubrication System	Specific Oil consumption	(% of fuel consumption)	0.1			
	Total Engine Oil Cap. w/filter	qt (L)	3.38 (12.8)			
	Oil Filter Type		Cartridge			
Engine Electricals	Battery Charging Alternator	Volts, Ground	12V, negative			
	Battery Charging Alternator	Rated amps	90			
	Recommended Battery Cold Crank	CCA amps	800			
	Starter Motor	Volts, Ground	12V, negative			
Operation	Temperature and Altitude Losses		Consult Factory			

OPTIONAL EQUIPMENT

Cooling System

- Remote Radiator
- Jacket Water Heater
- Crankcase Oil Heater

Fuel System

- Fuel/Water Separator
- Day Tank
- Above Ground Fuel Tank
- Auxiliary Fuel Pump
- Sub-Base Fuel Tank
 - Double Wall
 - UL Listed

Exhaust System

- Industrial Grade Muffler
- Residential Grade Muffler
- Critical Grade Muffler
- Super Critical Grade Muffler

Start System

- Battery Nicad

- Battery Warmer Plate
- Battery Charger
 - Automatic Float Equalizing
 - Trickle

Switchgear

- Main Line Circuit Breaker
 - Shunt trip
 - Auxiliary switch
- Automatic Transfer Switch
- Paralleling
- Protective Relays

Generator

- Permanent Magnet Excitation
- Space Heaters
- Temperature Rise Detectors

Control Panel

- Emergency stop button
- Microprocessor Control Panel
- NFPA 110 Ready


- Remote Annunciation Panel
- Audible Alarm

General

- Spring vibration isolators
- Automatic Transfer Switch
- Metal Enclosure
 - Weather Resistant
 - Sound Attenuated
 - Aluminum
- Interior lights AC or DC
- Trailer
- Export Packaging
- Special Testing
- Warranties
 - ____ Year

For Other Options Consult

DIMENSIONS AND WEIGHT



	Units	Open Unit	Enclosed Unit	Sound Att. Unit
Length	In. (mm)	89.5 (2273.3)	89.5 (2273.3)	109 (2768.6)
Width	In. (mm)	37 (939.8)	37 (939.8)	37 (939.8)
Height	In. (mm)	60 (1524)	64 (1625.6)	64 (1625.6)
Weight	Lbs (kg)	2311 (1048)	2473 (1122)	2500 (1134)

General configuration for reference only, do not use these dimensions for installation purposes. Contact your local dealer for certified drawings.